

SIDEWINDER® JAW CLAMP

SADDLE FUSE 4" BRANCH SADDLES & TAPPING TEES ONTO ALL MAIN SIZES



MADE FOR

UNDERGROUND
CONSTRUCTION



The standard Sidewinder fusion machines saddle fuse branches, tapping tees and service fittings onto mains from 1 ¼" to 4" IPS. Two configurations are available: jaw clamping and chain clamping. For main sizes larger than 4" IPS, a chain extension kit can be added to the chain clamping models. Both Sidewinders are DataLogger® compatible for documenting the fusion process.

STANDARD FEATURES

- ✓ Manually operated
- ✓ Split nut design for ease of applying and holding pressure
- ✓ Available as a compact unit for tighter confines and smaller fittings
- ✓ Microprocessor-controlled heater with Teflon-coated anti-stick plates
- ✓ Quick-release system for easy heater removal
- ✓ 4 pressure ranges
- ✓ DataLogger® compatible
- ✓ Heater guide pins aid in alignment of heater on main pivot release master for easy heater removal



DataLogger
COMPATIBLE

ADDITIONAL IMAGES



SPECIFICATIONS

MODELS

ASW00130	1,500 PSI Gauge
ASW00131	1,000 PSI Gauge
ASW00132	600 PSI Gauge
ASW00133	300 PSI Gauge

WEIGHTS

Machine	26 lbs. (11.8 Kg)
Shipping Weight	35 lbs. (15.9 Kg)

MACHINE DIMENSIONS

Machine Length	7.8" (196.8mm)
Machine Width	10.5" (266.7mm)
Machine Height	28" (711.2mm)

SHIPPING DIMENSIONS

Length	14" (355.6 mm)
Width	14" (355.6 mm)
Height	30" (762 mm)

INCLUDES

Fusion machine, 3" pivot master and screw/driver kit. Heaters and adapters are sold separately.